

Relais	1	2	3	4	5	6	7	
Atténuation dB	0.50 dB	1.00 dB	2.00 dB	4.00 dB	8.00 dB	16.00 dB	32.00 dB	
R Série	2.80K	5.49K	10.20K	18.70K	30.10K	42.20K	48.70K	
R Parallèle	845.00K	412.00K	191.00K	84.50K	33.20K	9.31K	1.30K	49.90K

Position								Atténuation
1								0.00
2	1							-0.50
3		1						-1.00
4	1	1						-1.50
5			1					-2.00
6	1		1					-2.50
7		1	1					-3.00
8	1	1	1					-3.50
9				1				-4.00
10	1			1				-4.50
11		1		1				-5.00
12	1	1		1				-5.50
13			1	1				-6.00
14	1		1	1				-6.50
15		1	1	1				-7.00
16	1	1	1	1				-7.50
17					1			-8.00
18	1				1			-8.50
19		1			1			-9.00
20	1	1			1			-9.50
21			1		1			-10.00
22	1		1		1			-10.50
23		1	1		1			-11.00
24	1	1	1		1			-11.50
25				1	1			-12.00
26	1			1	1			-12.50
27		1		1	1			-13.00
28	1	1		1	1			-13.50
29			1	1	1			-14.00
30	1		1	1	1			-14.50
31		1	1	1	1			-15.00
32	1	1	1	1	1			-15.50
33						1		-16.00
34	1					1		-16.50
35		1				1		-17.00
36	1	1				1		-17.50
37			1			1		-18.00
38	1		1			1		-18.50
39		1	1			1		-19.00
40	1	1	1			1		-19.50
41				1		1		-20.00
42	1			1		1		-20.50
43		1		1		1		-21.00
44	1	1		1		1		-21.50

Relais	1	2	3	4	5	6	7	
Atténuation dB	0.50 dB	1.00 dB	2.00 dB	4.00 dB	8.00 dB	16.00 dB	32.00 dB	
R Série	2.80K	5.49K	10.20K	18.70K	30.10K	42.20K	48.70K	
R Parallèle	845.00K	412.00K	191.00K	84.50K	33.20K	9.31K	1.30K	49.90K

Position								Atténuation
45			1	1		1		-22.00
46	1		1	1		1		-22.50
47		1	1	1		1		-23.00
48	1	1	1	1		1		-23.50
49					1	1		-24.00
50	1				1	1		-24.50
51		1			1	1		-25.00
52	1	1			1	1		-25.50
53			1		1	1		-26.00
54	1		1		1	1		-26.50
55		1	1		1	1		-27.00
56	1	1	1		1	1		-27.50
57				1	1	1		-28.00
58	1			1	1	1		-28.50
59		1		1	1	1		-29.00
60	1	1		1	1	1		-29.50
61			1	1	1	1		-30.00
62	1		1	1	1	1		-30.50
63		1	1	1	1	1		-31.00
64	1	1	1	1	1	1		-31.50
65							1	-32.00
66	1						1	-32.50
67		1					1	-33.00
68	1	1					1	-33.50
69			1				1	-34.00
70	1		1				1	-34.50
71		1	1				1	-35.00
72	1	1	1				1	-35.50
73				1			1	-36.00
74	1			1			1	-36.50
75		1		1			1	-37.00
76	1	1		1			1	-37.50
77			1	1			1	-38.00
78	1		1	1			1	-38.50
79		1	1	1			1	-39.00
80	1	1	1	1			1	-39.50
81					1		1	-40.00
82	1				1		1	-40.50
83		1			1		1	-41.00
84	1	1			1		1	-41.50
85			1		1		1	-42.00
86	1		1		1		1	-42.50
87		1	1		1		1	-43.00
88	1	1	1		1		1	-43.50

Relais	1	2	3	4	5	6	7	
Atténuation dB	0.50 dB	1.00 dB	2.00 dB	4.00 dB	8.00 dB	16.00 dB	32.00 dB	
R Série	2.80K	5.49K	10.20K	18.70K	30.10K	42.20K	48.70K	
R Parallèle	845.00K	412.00K	191.00K	84.50K	33.20K	9.31K	1.30K	49.90K